




The IPS4184E / IPS4188E is outdoor fitted Day & Night 1080P HD WDR PTZ Dome IP Camera that in compliance with LILIN's already established HD PTZ series of cameras. The camera can be powered through High Power over Ethernet, which complies with the PoE standard IEEE 802.3at. The high-speed domes are capable of streaming HD video at up to 30 FPS. Featuring LILIN's Wide dynamic Range (WDR) feature, the IPS4184E / IPS4188E captures highlights and shadows simultaneously, eliminating pixilation and smear. Combine this with Digital noise reduction technology and adaptive tone reproduction and the contrast of images in bright or dark areas is dramatically improved. Capable of making 360° continuous rotations, users can accurately position the camera to identify specific targets.

FEATURES :


- 18X Optical zoom Lens(4.7 – 84.6mm)
- HD 3 megapixel CMOS image sensor
- True H.264 AVC/MPEG-4 part 10 real-time Video compression
- H.264 and Motion JPEG multi-profile Video streaming
- Wide dynamic range
- Digital noise reduction Function
- Sens. Up Function
- Dynamic privacy zone mask
- 2-way audio supported
- ONVIF supported
- Weatherproof IP 66

DIMENSIONS : (Unit : mm)

Ø 210 x 332



INSTALLATION HOLE SITE DIAGRAM :



SPECIFICATION :

Name	18X Day & Night 1080P HD WDR PTZ Dome IP Camera (Outdoor)			
Model	IPS4184E		IPS4188E	
Power supply	AC24V	PoE+	AC100 - 240V	PoE+
Power consumption	37W (with Heater)	14W (not Heater)	48W (with Heater)	14W (not Heater)
Ambient operating temperature	-10°C - + 50°C (14°F - 122°F) / PoE+ -40°C - + 50°C (40°F - 122°F) / AC			
Image pick-up device	1/2.8 Type Exmor CMOS Sensor			
Effective pixels	2096 (H) x 1561 (V) = 3,269,760 (pixels)			
Total number of pixel	2144 (H) x 1588 (V) = 3,404,672 (pixels)			
Scanning system	Progressive scan			
Video output	CVBS 1.0 Vp-p / 75 Ω BNC			
Minimum illumination	0.1 lux (F1.6, 50IRE)			
IP rating	IP66			
Operating humidity	0% - 90%			
Dimension	332 mm (H) x 210 mm (V)			
Weight	3200 g			
Heater activation	On: 15°C, Off: 25°C			
Fan activation	On: 35°C, Off: 25°C			
Pan & tilt				
Panning range	360° Endless			
Panning mode	Manual , auto , manual position , sequential position			
Panning speed	Manual approx. 0.15°/s - 120°/s 8 Steps, Preset approx. 1°/s - 255°/s, Alarm Trigger Speed 360°/s			
Tilting range	- 6° - + 96°			
Tilting mode	Manual , auto , manual position , sequential position			
Tilting speed	Manual approx. 0.15°/s - 120°/s 8 Steps, Preset approx. 1°/s - 255°/s, Alarm Trigger Speed 360°/s			
Lens				
Zoom ratio	18X Optical zoom			
Focal length	4.7 mm (WIDE) to 84.6.0 mm(TELE)			
Minimum aperture ratio	1 : 1.6 (Wide) - 3.5 (Tele)			
Minimum object distance	10 cm (WIDE end), 1.5m (TELE end)			
Iris range	F1.6 - 360 , Close			
Angle field of view	54.1 degrees (WIDE end), approx. 3.2 degrees (TELE end), (1080P mode)			
Main functions				
Control function	Pan and Tilt / Zoom and Focus / Iris and ICR / 128 Preset Position / Home Position			
Zoom speed	Slow / MID. / Fast Selectable [Fast : Approx. 5.0 Second(Tele to Wide) in Manual Mode]			
Focus speed	Slow / MID. / Fast Selectable [Fast : Approx. 5.0 Second (Far to Near) in Manual Mode]			
Auto focus	Auto / One Push Focus			
Iris	Auto / Manual			
Day & Night	Day / Night / Auto / Schedule			
Sense up (Slow shutter)	OFF / ON			
Electronic shutter speed	1/1 to 1/10,000			
Exposure mode	Auto / Manual			
Back light compensation	OFF / ON			
Digital Wide dynamic range (atr)	OFF / ON			
Sharpness	Adjustable			
White balance	ATW / AWC / Manual (1700K - 11000K)			
Auto gain control	0 - 28dB (12 Step)			
Digital noise reduction	(2D) OFF / LEVEL=1 - 5			
Dynamic privacy zone mask	OFF / ON (Up to 14 area)			
Digital effect	OFF / Mirror			
Alarm input / output	6 Input (TTL 5Vdc) , 2 Output (0.5A 120Vac,1A 24Vac)			
Schedule setting	OFF / Auto mode / Preset Position			
Auto mode	OFF / AUTO / SEQ / TOUR			
Network				
Video compression	H.264, Motion JPEG			
Resolution	1080P(1920 x 1080) , 720P(1280 x 720) , D1(720 x 480) , CIF(352 x 240)			
Frame rate	H.264 : up to 30 FPS at 1080P(1920 x 1080) Motion JPEG : up to 30 FPS at D1(720 x 480)			
Video streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast			
Video bitrate	128 Kbps to 5 Mbps Frame rate and bitrate controllable on-the-fly VBR / CBR / GOP supported			
Security	Base64 HTTP encryption / Multiple user access levels with password protection			
Max number of online users	10 user accounts available			
User accounts	8 simultaneous users			
OSD	Text overlay for date, time, and camera name			
Alarm function	Image upload over FTP and E-mail by alarm / motion detection			
CPU, memory	Embedded SoC ARM11, 528MHz, 256MB DDR2, 256MB flash memory			
Web PTZ control	Pan , tilt , zoom in / out , absolute position, and video-click-n-move			
PTZ preset scheduling	Yes, via web interface			
Maintenance	Firmware update via HTTP Firmware available at web site			
Network interface	10Mbps / 100Mbps , RJ-45			
Client pc requirement	OS : Windows 2000 , Windows XP , Windows Vista, Windows 7 Browser : Windows Internet Explorer 6.0 or above CPU : intel pentium 4 1.8GHz or above RAM : 1GB or above, Independent Display Card			
Network protocols	IPv4, IPv6, TCP, UDP, HTTP, SMTP, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S, SNMP, Bonjour			
Mobile phone	iPhone, iPad, and Android support			
System integration	ONVIF & LILIN HTTPAPI			
Central management system	CMX 3.6 / Navigator 3.8 support			
Video display	LILIN Universal ActiveX & LILIN Java Applet			
OS	Embedded Linux 2.6.32			
Two-way audio	G.711			
SD card recording	Support Micro SD/SDHC/SDXC card for circular recording (card is not included)			
D/N quality setting	Yes			
IP address filter	Yes			
Multi IP address	Yes			
Alarm event actions	Yes			
Alarm weighted mode	Yes			
RTSP Authentication	On / Off			
Warranty	Warranty 3 years, but lens and motors are limited in 1 year			

