

1.0 Manufacturer

Merit LILIN ENT. Co. Ltd
No. 20, Wu-Kong 6 Rd.,
Wu-Ku Industrial Zone Wu-Ku District,
New Taipei City, Taiwan R.O.C.

2.0 Warranty

Manufacturer shall warrant the camera to be free from defects in material and workmanship for three years from the purchase date.

3.0 General Specifications

The camera shall be LILIN AHD654A3.6.

Video Performance

- A. The camera shall have a minimum light requirement of 0.2 Lux at F1.8 in color mode.
- B. The camera shall have a minimum light requirement of 0 Lux with IR led on.

Power

- A. Power requirement for the camera shall be DC12V, 5W.

Infrared LED

- A. The camera shall support IR distance at 20m.
- B. The camera shall support peak wavelength at 850nm.
- C. The camera shall support beam spread at 48° (H) x 30° (V).

Sensor

- A. The camera shall use the 1/3" CMOS image sensor.
- B. The camera shall produce a maximum resolution of 2,688 (H) × 1,520 (V).

Lens

- A. The camera shall support 3.6mm fixed lens.
- B. The camera shall support F2.0 fixed iris.
- C. The camera shall support 72.2° horizontal angle of view.
- D. The camera shall support 52.9° vertical angle of view.
- E. The camera shall support 94.3° diameter angle of view.

Mechanical

- A. The camera shall not exceed a dimension of Ø 115 x 91mm (H) approximately.
- B. The camera shall not exceed a weight of 370g approximately.

Video Input / Output

- A. The camera shall provide AHD 4MP and CVBS.

Environmental

- A. The camera shall be operated in temperature range of - 40°C – + 50°C / - 40°F – 122°F.

Video Resolutions

- A. The camera shall support 2560x1440@30 FPS.

IR-cut Filter

- A. The IR cut filter shall be able to support automatic switch from color mode to monochrome.

Scanning System

- A. The camera shall use a progressive scan image sensor.

UTC

- A. The UTC shall be able to support AHD-Coaxial protocol.

Picture Effects

- A. The camera shall provide mirror, v-flip and flip.

Video Quality

- A. The camera is able to specify its shutter speed for min and max range 1/30s to 1/50000s for various environments.
- B. The camera shall support LSC.
- C. The camera shall support 2D WDR.
- D. The camera shall support 2D noise reduction.
- E. The camera shall support auto gain control up to 55dB.

Languages

- A. The camera shall support English, Traditional Chinese, Simplified Chinese, Spanish, Italian, Turkish, German, Polish, Portuguese, Dutch, Russian, French, Japanese languages.

System

- A. The camera shall provide NTSC and PAL system settings.

Certifications

- A. The camera shall be CE compliant.
- B. The camera shall meet IP66 standard against water and dust ingress.
- C. The camera shall meet IK10 vandal resistant rating.

4.0 Installation

- A. All equipments shall be tested and configured based on the manufacturer guide line prior to installation.
- B. All the products shall be updated for the latest firmware.
- C. All the products shall be changed for the default username and password prior to installation.

5.0 Environmental Green Policy

- A. The specified camera shall be manufactured in accordance with ISO 14001.
- B. The specified camera shall be compliant with the EU directives RoHS and WEEE.
- C. The specified camera shall be compliant with the EU regulation REACH.

END OF SECTION