

1.0 Manufacturer

Merit LILIN ENT. Co. Ltd
No. 20, Wu-Kong 6 Rd.,
Wu-Ku Industrial Zone Wu-Ku District,
New Taipei City, Taiwan R.O.C.

2.0 Warranty

Manufacturer shall warrant the camera to be free from defects in material and workmanship for three years from the purchase date.

3.0 General Specifications

The network camera shall be LILIN MR6822E2 camera.

Video Performance

- A. The camera shall have a minimum light requirement of 0.01 Lux at F1.8 in color mode, 0.003 Lux at F1.8 in B/W mode, or 0 Lux if IR on.
- B. The camera shall have a minimum light requirement of 0 Lux with IR led on.

Power

- A. Power requirement for the network camera shall be DC12V $\pm 10\%$, 4.5W or PoE, 5.5W.
- B. The camera shall provide power consumption DC12V at 5.5W.

Sensor

- A. The camera shall use the 1/2.8" CMOS image sensor.
- B. The camera shall produce a maximum resolution of 1945 (H) x 1097 (V) = 2,133,665 pixels.

Certifications

- A. The camera shall be compliant with CE certifications.
- B. The camera shall be compliant with FCC Class B certifications.
- C. The camera shall be rated to IP67 standard against water and dust ingress.

PC Requirements

- A. The PC CPU requirement shall be Intel I3 or above for the camera.
- B. The camera shall support Windows 7 64 bit, Windows 8 64 bit, Windows 10 64 bit.
- C. The PC memory RAM shall be at least 4GB or above for the camera.

Mechanical

- A. The camera shall not exceed a dimension of $\varnothing 73\text{mm} \times 62\text{mm}$ approximately.
- B. The camera shall not exceed a weight of 230g approximately.

Video Streaming

- A. Video streaming format shall meet the standard H.264, and in order to provide better quality and compression rate, shall support H.264 main profile, H.264 high profile and also shall support Motion JPEG.
- B. The camera shall provide RTP/HTTP, RTP/TCP, RTP/UDP.
- C. The camera shall provide 3 streaming with combine compression and resolution at same time for various Internet or Intranet applications.
- D. The camera shall support VBR, CBR, GOP adjustable, fixed bitrate range, smart H.264 encoding mode.
- E. The camera shall provide 4 of resolution in browser for user easy to change resolution.

Network Security

- A. The camera shall support up to 10 users for accessing the streaming.
- B. The camera shall support multiple user access levels with password protection.

Authentication

- A. The camera shall support base64 HTTP encryption, digest HTTP authentication, IP address filtering, RTSP authentication, HTTPS DDNS via HTTP.

Integration

- A. The camera shall be able to be accessed by the mobile device (IOS and Android).
- B. The camera shall conform to the ONVIF Profile S standard and provide official documentation.
- C. The camera shall support LILIN Navigator Enterprise 2.0.
- D. The camera shall support 3rd. party VMS through LILIN HTTP API.

Web Browser

- A. The camera shall support IE 11.

Alarm Events

- A. The camera shall support motion detection, tamper detection, audio detection and push service for smartphone.

Standard IVS

- A. The camera shall support standard IVS: advanced motion detection, tripwire, object counting and semaphore detection.

Alarm Notification

- A. The camera shall provide alarm notification with SMTP, FTP, HTTP post, SAMBA.

Environmental

- A. The camera shall be operated in following temperature range: -40°C – +50°C/-40°F – 122°F.

Lens

- A. The camera shall support fixed lens at 2.8mm.
- B. The camera shall support fixed iris at F1.8.
- C. The camera shall support horizontal angle of view at 84°.
- D. The camera shall support vertical angle of view at 43.3°.
- E. The camera shall support diameter angle of view at 99.4°.

Infrared LED

- A. The camera shall support IR distance at 30m.
- B. The camera shall support peak wavelength at 850nm.
- C. The camera shall support beam spread at 60°, 90°.

Video Resolutions

- A. The network camera shall be able to produce images in 1920x1080 (1080P), 1280x960, 1280x720 (720P), 720x480 (D1), 720x576 (D1), 640x480, and 352x240 (CIF).

Maximum Frame Rate

- A. The camera shall produce 30 FPS @ 1920 x 1080 resolution with H.264 video compression.
- B. The camera shall produce 30 FPS @ 1920 x 1080 resolution with MJPEG video compression.

IR-cut Filter

- A. The IR cut filter shall be able to support color (day), monochrome (night), auto, schedule.

Scanning System

- A. The camera shall use a progressive scan image sensor.

Picture Setting

- A. The camera shall provide brightness, contrast, hue, saturation and sharpness.

Picture Effects

- A. The camera shall provide lens distortion correction (LDC).

White Balance

- A. The camera shall provide the white balance settings including: auto, tungsten, indoor, fluorescents 1, fluorescents 2, outdoor 1, custom.

Video Quality

- A. The camera is able to specify its shutter speed for min and max range 1/30(1/25) s to 1/30000s for various environments.
- B. The camera shall support 2D WDR.
- C. The camera shall support HDR at 100dB.
- D. The camera shall support 3D noise reduction.
- E. The camera shall support privacy mask up to 4 zones.
- F. The camera shall provide the sense up settings including: off, 1 frame, 2 frames.
- G. The camera shall support Sense up+.
- H. The camera shall support auto gain control up to 66dB.
- I. The camera shall support lens distortion correction.
- J. The camera shall support S/N ratio.

Network

- A. The camera shall support 10Base-T, 100Base-TX.
- B. The camera shall support LILIN API (CGI).
- C. The camera shall support display OSD date, time, camera name.

CPU

- A. The camera shall support up to Embedded SoC ARM Cortex-A9, 600MHz.
- B. The camera shall support up to 256MB DDR3.

Video Display

- A. The camera shall provide the video display settings including: LILIN Universal Active X, LILIN Java Applet and HTML 5.

OS

- A. The OS of the camera should be embedded Linux 3.10.

Protocols

- A. The camera shall support the following network protocols: IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, SIP, MQTT, QoS, SNMP Trap, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S, SDDP, Bonjour and 802.1x.

Languages

- A. The camera shall support the following languages: English, Traditional Chinese, Simplified Chinese, Spanish, Italian, Turkish, Russian, Korean, French, Arabic, Hungarian, Japanese.

Others

- A. The camera shall support multi IP addresses and MAC address filter.

4.0 Installation

- A. All equipments shall be tested and configured based on the manufacturer guide line prior to installation.
- B. All the products shall be updated for the latest firmware.
- C. All the products shall be changed for the default username and password prior to installation.

5.0 Environmental Green Policy

- A. The specified camera shall be manufactured in accordance with ISO 14001.
- B. The specified camera shall be compliant with the EU directives RoHS and WEEE.
- C. The specified camera shall be compliant with the EU regulation REACH.

END OF SECTION