

1.0 Manufacturer

MERIT LILIN ENT. CO. LTD
No.20, Wu-Kong 6 Rd.,
New Taipei Industrial Park,
Wugu District, New Taipei City,
Taiwan R.O.C.

2.0 Description

LILIN L series NVR200L multi-touch standalone Network Video Recorder is a plug-n-play and cost-effective video surveillance system for SOHO and SMB users to record and navigate their IP based security cameras.

LILIN NVR L series systems support up to 6TB storage capacity. With a total of 40Mbps of bandwidth available, the L series NVRs are able to support up to 16 cameras at high definition resolution in real time as well as other configurations.

The user interface is intuitive with all the features that end users need for daily video surveillance operations – video recording, playback / live view of recorded video.

Full LILIN CMX / NAV software support, Web based remote viewing, IOS, and Android support. With LILIN's unique IP Scan technology, you can locate all the cameras on the network and imports a preview picture of each channel to help with identification, which greatly speeds up commissioning.

Manufacturer shall warrant the NVR200L, NVR Series, to be free from defects in material and workmanship for three years from the installation date.

3.0 General Specifications

NVR shall support frame rate of single channel up to 1080P 60 FPS.
NVR shall support 200 FPS maximum frame rate.
NVR shall support 1 / 4 / 8 / 9 / 13 / 16, sequence mode, freeze at split screen.
NVR shall support USB multi-touch screen.
NVR shall support H.264 network video format.
NVR shall support 40 Mbps maximum network throughput.
NVR shall support up to 64X on live and playback at digital zoom.
NVR shall support network camera.

NVR shall support CIF - 3M recording resolution.
NVR shall support recording schedule with each channel 24 hours 7 days time table, recording mode configurable.
NVR shall support automatic recording day calculator.

NVR shall support alarm event actions for motion grid, network camera event.
NVR shall support IOS, Android, email, FTP, buzzer alarm notification recording.
NVR shall support alarm event, operation and configuration full reports exporting over HTTP or USB.

NVR shall support playback search for alarm event, operation event, system event, meta data event, time search.
NVR shall support 16ch synchronous playback display.
NVR shall support CIF - 3M playback resolution feature for live monitoring and video playback.
NVR shall support up to 1080P 60 FPS playback max frame rate
NVR shall support fast rewind 2× ~ 64× / fast forward 2× ~ 64× / step forward playback speed.

NVR shall support Internal HDD 2 × 3.5" HDD, up to 6TB supported.
NVR shall support S.M.A.R.T monitoring, file system de-fragmentation.
NVR shall support USB flash disk backup, up to 32 GB supported.
NVR shall support network backup via HTTP / FTP.
NVR shall support external USB DVD/ RW

NVR shall support remote playback manager, backup, multiple NVRs file download and multi-channel playback.

NVR shall support 1080P HDMI output.

NVR shall support audio input of 16 ch network camera, G.711 8K.

NVR shall support audio output of RCA × 1 (0.7Vp-p, 300 Hz to 3 KHz).

NVR shall provide network ports of RJ-45 Gigabit Ethernet × 1.

NVR shall support direct internet browser access and multiple users access.

NVR shall support ARP / TCP/IP / UDP / HTTP / SMTP / FTP / DDNS / PPPoE / NTP / RTP / RTSP / DHCP / SDDP protocols.

NVR shall support PTZ protocol via HTTP.

NVR shall support IOS / Android.

NVR shall support WS-Discovery and IP scan, automatic quick IP address setup for network cameras.

NVR shall support Navigator.

NVR shall provide user authentication with feature configurable.

NVR shall support English, Traditional Chinese, German, Italian, Portuguese, Spanish, French, Turkish, Hungarian, Polish, Russian, Arabic, Simplified Chinese.

NVR shall support daylight saving, NTP, external USB GPS time sync.

NVR shall support optional.

NVR shall support mouse click, drag and scroll.

NVR shall provide CPU of ARM Cortex A9.

NVR shall provide OS of embedded Linux Kernel 2.6.

NVR shall provide WDT of hardware watchdog timer.

NVR shall support backlight saving with adjustable idle time 30 ~ 60 sec.

NVR shall provide power supply of DC 12V, 5A, 60W.

NVR shall work within operating temperature of 0°C ~ 45°C.

NVR shall work within operating humidity of 5% ~ 80%.

NVR shall not exceed dimensions of 360 × 316 × 60 mm.

NVR shall not exceed weight of 3 kg without hard drive.

4.0 Installation

All equipments shall be tested and configured based on the manufacturer guide line prior to installation

All the products shall be updated for the latest firmware.

All the products shall be changed for the default username and password prior to installation.

5.0 Environmental Green Policy

The specified camera shall be manufactured in accordance with ISO 14001.

The specified camera shall be compliant with the EU directives RoHS and WEEE.

The specified camera shall be compliant with the EU regulation REACH.

END OF SECTION