

1.0 Manufacturer

Merit LILIN Ent. Co., Ltd.
No. 20, Wugong 6th Road,
Wugu District, New Taipei City 248

Manufacturer shall warrant the camera to be free from defects in material and workmanship for two years from the purchase date.

2.0 Camera Network Description

The Day & Night 2-Megapixel 1080P HD Auto Focus Vandal Resistant Dome IP Camera described shall be a LILIN model number ZD6122EX3 or equivalent. The camera described shall be an industrial IP67 grade, high sensitivity megapixel camera using multiple-profile video streaming of H.264 and Motion JPEG technologies, built-in IR cut filter mechanism, auto color & mono switching, back light compensation, day & night applications for 24-hr surveillance, effective low light performance, and is PoE (IEEE 802.3af compatible) and/or can be directly powered using DC12V, 8W.

3.0 General Specifications

- 3.1 The Day & Night 2-Megapixel 1080P HD Auto Focus Vandal Resistant Dome IP Camera shall incorporate a 1/2.7" Progressive scan CMOS sensor with 1920 (H) x 1080 (V) effective pixels. The network camera shall be able to produce images in 1080P, 720P, D1 or CIF resolution. The camera shall have a minimum light requirement of 0.1 lux at F1.4 in color mode (Low Light Mode). The video output level shall be CVBS 1.0Vp-p, 75Ω, and RCA connector.
- 3.2 The camera shall support 2-way audio function.
- 3.3 The camera shall produce 30 frames per second at 1080P resolution with H.264 video compression or produce 30 frames per second at 1080P resolution with Motion JPEG video compression.
- 3.4 The camera shall provide three streaming at same time for various Internet or Intranet applications.
- 3.5 The camera shall compliant with IP67 Weather and Dust resistance rating.
- 3.6 The camera shall have at least 256MB of RAM.
- 3.7 The camera shall provide a TCP/IP protocol video output via a RJ-45 Ethernet connection.
- 3.8 The camera shall provide Micro SD/SDHC for circular local recording.
- 3.9 User and Administrator password protection levels are provided.
- 3.10 The camera shall provide two sets of sensors or video quality for day and night that the setting can be programmed based on individual schedule(s).
- 3.11 The camera is able to specify its shutter speed for min and max range for various environments. (1/30(25s ~ 1/8,000s)
- 3.12 The camera shall provide 3D noise reduction feature.
- 3.13 The camera shall provide WDR and BLC features.
- 3.14 The camera shall provide privacy mask features.
- 3.15 The camera shall provide alarm, motion, tampering, and face detection features.
- 3.16 The camera shall provide PoE (IEEE 802.3af compatible) input.
- 3.17 The camera shall provide video mirror and flip features.
- 3.18 A recessed mechanical reset button shall be provided to return the camera to factory default

settings.

- 3.19 The camera shall provide auto focus with zoom and/or focus motorized lens.

4.0 Camera Networking Requirements

- 4.1 The camera shall incorporate a built-in web server.
- 4.2 The camera shall provide integrated support for IP, TCP, UDP, HTTP, SMTP, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTCP, RTSP, Telnet, ICMP, IGMP, and ONVIF protocols.
- 4.3 The camera shall provide FTP services for sending JPEG snapshots based on scheduling and/or continuously sent with various time pattern, prefix, and postfix for JPEG file names that it can achieve better FTP system integration.
- 4.4 The camera shall provide email service for sending JPEG snapshots for at least 5 different recipients.
- 4.5 No unique or proprietary client software shall be required for viewing or controlling the camera.
- 4.6 The camera shall be user configurable and the administrator may functionally or aesthetically modify the camera's web pages.
- 4.7 The camera shall provide 3G mobile remote live monitoring capability – Alarm PushVideo on smartphone devices.
- 4.8 Multiple cameras installed shall be connected and managed by Center Management Software (CMX Software). Cameras can be grouped in the CMX Software. Camera groupings in CMX Software can be assigned for certain user(s) for user management purpose.
- 4.9 The camera shall provide IP filter to isolate a particular IP address for safety and related possible conditions.
- 4.10 The camera shall provide NTP (Network Time Protocol) feature so that the camera is able to connect to NTP network.
- 4.11 The camera shall provide OSD (on-screen display) feature which includes time display and device name display.
- 4.12 The Web server of the camera shall provide system log information for administrator(s) to view videos and operation details.
- 4.13 The camera shall provide alarm event notification via external alarm outputs on detections on audio, motion, and network lost.
- 4.14 The camera shall have Micro SD/SDHC card video playback function so that users can store designated videos into the Micro SD/SDHC card without using an extra media player to support.
- 4.15 The camera shall provide various alarm event outputs: i.e. GPIO (general purpose input/output), FTP (file transfer protocol) and email notification services to notify the users.

The camera shall not exceed a dimension of body: Ø 145mm x 130mm and weigh no more than 960g. Power requirement for the network camera shall be DC12V, 8W / PoE, 9.5W. The operating temperature for video camera shall be -40°C ~ +50°C (-40°F ~ 122°F). The camera manufacturer shall be ISO 9001 certified and Camera shall comply with CE.

5.0 Minimum Performance Specifications

6.0 Day & Night 1080P HD Auto Focus Dome IP Camera			
Model			ZD6122EX3
Lens	Focal Length		3～10.5mm (zoom / focus motorized)
	Iris		F1.4
	Angle of View	H	91.2° ～25.5°
		V	68.4° ～19.1°
		D	114° ～31.9°
Pick Up Element			1/2.7" CMOS image sensor
Effective Pixels			1920 (H) x 1080 (V) = 2,073,600 (pixel)
Chip Size			5.856mm (H) x 3.276mm (V)
Scanning System			Progressive Scan
Infrared Cut Filter			Auto / Schedule / Day (Color) / Night (Mono)
Min. Illumination			0.1 Lux at F1.4 (Low Light Mode)
White Balance			Auto / Tungsten / Indoor / Fluorescents 1 / Fluorescents 2 / Outdoor 1 / Outdoor 2
Back Light Compensation			Off / On
Electrical Shutter			1/30(25)s ～1/8,000s
Sense Up			Off / 1 Frame / 2 Frames / 3 Frames / 7 Frames
Sense Up Plus			Yes
Auto Gain Control			36 dB Variable Gain
3D Noise Reduction			Off / 1～32 Selectable
2D WDR			Off / One
Privacy Masking			Off / On (4 zones)
Image Effects			Brightness, Contrast, Hue, Saturation, Sharpness, Mirror, Flip
Auto Focus			One Push
Live Video Output			CVBS 1.0Vp-p, 75 ohm, RCA connector
Audio In / Output			Mono, 1.4 Vp-p, 50 KΩ, 3.5mm phone jack
IP Rating			IP67
Vandal Resistant Rating			IK10
Operating Temperature			-40℃ ～+50℃ (-40°F ～122°F)
Dimension			Ø145 x 130mm
Weight			960g
Power Supply			DC12V ± 10% / PoE (IEEE 802.3af compliant)
Power Consumption			DC12V, 8W / PoE, 9.5W
NETWORK			
Video Compression			H.264, Motion JPEG
Resolution			1080P (1920 x 1080), 720P (1280 x 720), D1(720 x 480), CIF (352 x 240)
Multiple Profile	Profile #1		H.264: up to 30FPS @ 1920 x 1080, MJPEG: up to 30FPS @ 720 x 480

	Profile #2	H.264: up to 30FPS @ 1280 x 720, MJPEG: up to 30FPS @ 352 x 240
	Profile #3	H.264: up to 30FPS @ 1920 x 1080, MJPEG: up to 30FPS @ 720 x 480,
	Profile #4	H.264: up to 30FPS @ 720 x 480, MJPEG: up to 15FPS @ 1920 x 1080
Video Streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast	
Video Bitrate	128Kbps ~ 5Mbps	
	Frame rate and bit rate controllable on-the-fly	
	VBR / CBR / GOP supported	
Security	Base 64 HTTP encryption	
	Multiple user access levels with password protection	
	10 user accounts available	
Users	8 simultaneous users	
ePTZ & Digital Zoom	Yes, ROI is supported	
OSD	Text overlay for date, time, and camera name	
Alarm Function	Alarm / motion / tampering / face detection triggering recording into SD card	
	Image upload over FTP and email by face / tampering / audio / motion detection	
CPU, Memory	Embedded SoC ARM11, 528MHz, 256MB DDR2, 256MB flash memory	
Maintenance	Firmware available at website	
Network Interface	10Mbps / 100Mbps Base-T, RJ-45	
PC Requirement	OS: Windows 2000, Windows XP, Windows Vista, Windows 7	
	Browser: Windows Internet Explorer 6, 7, 8	
	CPU: Intel Pentium 4 1.8 GHz or above	
	RAM: 1GB or above, Independent Display Card	
Network Protocols	IP, TCP, UDP, HTTP, SMTP, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF	
Mobile phone	iPhone, iPad, and Android support	
System Integration	ONVIF & LILIN HTTP API	
CMX	CMX HD3.6 support or equivalent	
Video Display	LILIN Universal ActiveX & LILIN Java Applet	
OS	Embedded Linux 2.6.32	
Two-way Audio	G.711 / PCM	
SD Card Recording	Support Micro SD / SDHC card for circular recording or record only there is incidents (triggered by alarm feature).	
Alarm Input / Output	Digital 1 input (TTL, +3 ~ 5V) / 1 Output (N.O.)	

*Please submit ISO 9001, CE, IP67, IK10 certificates.

*This specification is intended for use by the design/construction professional and any user of LILIN products to assist in developing project specifications for security and video surveillance systems.