

AHD261


D/N 720P AHD VARI-FOCAL Dome IR Camera



FEATURES:

- Video Output: AHD 720P / Analog 1280H
- AHD Cameras transmit data that is not encoded resulting in no process and no delay real time and complete transmission.
- Long transmission distance—Coaxial cable (3C/5C): 300M
- Seamless compatibility with the standard Analog equipment
- Automatically activates IR LED: Blow 10Lux

Ø128 x 100mm(H)



D/N 720P AHD VARI-FOCAL Dome IR Camera			
Model			AHD261AX4.2
Lens	Focal length		2.8 ~ 12mm
	Iris		F1.4
	Angle of view	H	91° ~ 28°
		V	67.5° ~ 21.2°
		D	120.8° ~ 36°
Power Input Voltage			DC12V ±10%
System			NTSC or PAL
Pick Up Element			1/3" CMOS Image Sensor
Effective Pixels			1,305 (H) x 977 (V)
Scanning System			Progressive Scan
Menu Control			OSD Control
Sync. Mode			Internal
Infrared Cut Filter			Auto Selectable, Automatic Switch from Color Mode to Monochrome
Resolution			1280 (H) x 720 (V) @ 30/25 fps
Minimum Illumination			0.01 Lux / F1.4, 0 Lux (IR On)
S/N Ratio			More Than 55dB (AGC Off)
Auto Gain Control			Auto (16 Steps)
White Balance			ATW / AWC / INDOOR / OUTDOOR / MANUAL / AWB
Shutter	Auto		1/60(1/50)S ~ 1/50,000S
	Manual		1/30(1/25)S, 1/60(1/50)S, FLK, 1/240S, 1/480S, 1/1,000S, 1/2,000S, 1/5,000S, 1/10,000S, 1/50,000S
Sens-Up			OFF / AUTO (X2 ~ X30)
D-WDR			OFF / ON / AUTO
Back Light Compensation			OFF / BLC / HSBLIC
Noise Reduction			2DNR & 3DNR
Defog			OFF / AUTO
Privacy masking			OFF / ON
Privacy masking Zone			4 Zones
OSD Language			ENG / CHN1 / CHN2 / GER / FRA / ITA / SPA / POL / RUS / POR / NED / TUR
Video Output			AHD720P / 1280H
Power Consumption			3.6W
Operation Temperature			- 10°C ~ + 50°C (-14°F ~ 122°F)
Infrared LED	Peak Wavelength		850nm
	Beam Spread		30°
	Radiant Distance		20M
Dimension			φ128 x 100mm(H)
Weight			325g