

AHD654A 3.6/6

D/N 4MP AHD VR DOME IR Camera



FEATURES:

- Video Output: AHD 4MP / CVBS
- Video without compression, no delay with high quality and real-time monitoring.
- Long transmission distance—Coaxial cable (3C/5C): 100M / 200M
- Seamless compatibility with the standard Analog equipment
- Automatically activates IR LED: Below 10Lux
- UTC function (AHD-Coaxial protocol)

D/N 4MP AHD VARI-FOCAL DOME IR CAMERA				
Model			AHD654A3.6	AHD654A6
Lens	Focal length		3.6mm	6mm
	Iris		F2.0	F1.8
	Angle of view	H	72.2°	46.5°
		V	52.9°	34.5°
		D	94.3°	59.3°
System			NTSC or PAL	
Infrared LED	Radiant Distance		20M	
	Beam Spread		48°(H) x 30°(V)	
	Peak Wavelength		850nm	
Pick Up Element			1/3" CMOS Image Sensor	
Effective Pixels			2,688 (H) x 1,520 (V)	
Scanning System			Progressive Scan	
Menu Control			OSD Control	
Resolution			2,560 (H) x 1,440 (V) @ 30/25 fps	
Sync. Mode			Internal	
Infrared Cut Filter			Auto Selectable, Automatic Switch from Color Mode to Monochrome	
Minimum Illumination			0.2 Lux / F1.8, 0 Lux (IR On)	
S/N Ratio			More Than 55dB (AGC Off)	
UTC			AHD-Coaxial protocol Supported	
Auto Gain Control			Auto (16 Steps)	
Shutter	Auto		1/30(1/25)S - 1/50,000S	
	Manual		1/30(1/25)S, 1/60(1/50)S, FLK, 1/240S, 1/480S, 1/1,000S, 1/2,000S, 1/5,000S, 1/10,000S, 1/50,000S	
D-WDR			OFF / ON / AUTO	
Noise Reduction			2DNR	
Sharpness			AUTO / OFF	
LSC			ON / OFF	
Digital Effect			MIRROR / V-FLIP / ROTATE	
OSD Language			ENG / CHN1 / CHN2 / GER / FRA / ITA / SPA / POL / RUS / POR / NED / TUR / JPN	
CE			Yes	
Video Output			AHD 4MP / CVBS	
Power Consumption			5W	
Operation Temperature			- 40°C ~ + 50°C (-40°F ~ 122°F)	
IP Rating			IP66	
Vandal Resistant Rating			IK10	
Dimension			φ 115(D) x 91mm(H)	
Weight			370g	
Power Input Voltage			DC12V ±10%	

No liability will be accepted for any errors or omissions. Design and specifications are subject to change without notice.