

IM15608

100 Meter Infrared Illuminator



Features

- Radiant distance up to 100m
- Infrared Wave Length 850nm
- IP67 rain and dust resistant
- Status Output support

Specification	
Maximum Radiant Distance	100m
LED Wave Length	850nm
Beam Angle	60°
LED Quantity	48 Units
LED Trun On	Sensor Auto Control, Adjustable Control Point / External Input Control
Status Output	Relay contact N.O., N.C., COM (24VDC,1A)
Mounting	Ceilling & Wall
IP Rating	IP67
Vandal Resistant Rating	IK10 (Casing)
CE	Yes, EMI Class A
FCC	Yes, EMI Class A
UKCA	Yes, EMI Class A
Starting Temperature	-10°C – +50°C (14°F – 122°F)
Operating Temperature	-40°C – +50°C (-40°F – 122°F)
Storage Temperature	-25°C – +60°C (-13°F – 140°F)
Humidity	0% – 90% RH
Casing Material	Aluminum alloy & Polycarbonate
Color (RAL Number)	Silver
Dimension	Main Body: 172 (W) x 242 (H) x 105 (D) mm with Bracket: 176 (W) x 260 (H) x 192 (D) mm
Weight	2400g
Power Supply	AC100 – 240V ±10%
Power Consumption	0.82A, 74W
Warranty Period	2 years