

MIC03

CONDENSER MICROPHONE

MIC
SERIES

- 3.5mm connector for IP cameras with Line IN
- Omnidirectional condenser microphone that covers a wide angle when recording
- -60dB high sensitivity for clear sound
- 5m shielded cable that reduces signal interference 3D noise reduction (MCTF)

Specifications

S / N Ratio	More than 60dB
Impedance	Low (2.2K ohm Max.)
Directional	Omnidirectional
Microphone Type	Electret Condenser Microphone
Sensitivity	-40±4dB(Omni) At 2.0 V, 2.2K Ohm, 0dB=1V/Pa 1KHz
Microphone Diameter	Ø18.5 × 40mm
Max. Operation Voltage	5 V
Standard Operation Voltage	2.0 V
Frequency	100 - 10KHz
Current consumption	0.5mA
Wire Spec.	Connect : Ø 3.5mm straight plug
Wire Spec.	Wire : Ø 3.6mm PVC
Wire Spec.	Wire Breaking Strength : Breaking shall not less than 5KGs
Wire Spec.	Total Resistance : Shall not exceed 0.3ohm per meter
Operating temperature	-25 - 70°C
Storage temperature	-40 - 80°C
Dimensions	Body : Ø18.5mm × 40mm , Wire : 5M±5%
Weight	121g

