

PLH-2812MA-5M



光學規格

	項目	描述			Tolerances
1	焦距	2.8-12mm(Real Value:3.47mm (W) ~ 9.85 mm (T))			±3%
2	相對孔徑	F1.86 (W) ~ F3.32(T)			±5%
3	成像靶面	Relative Illumination=35%: >φ6.9mm			--
4	成像範圍	0.8m~INF(W),1m~INF(T)			--
5	光學畸變	Image Circle=6.6mm:-51.4%(W),-4%(T)			--
6	主光角	9°			--
7	FOV (視角)	CMOS	W	T	--
		1/2.8" D6.480×H5.184×V3.888	122.6°×92.5°×66.9°	38°×30.4°×22.7°	
		1/2.7" D6.635×H5.376×V3.888	126.7°×96.6°×66.8°	38.9°×31.5°×22.7°	
		1/3" D6.084×H4.977×V3.499	112.6°×88.2°×59.8°	35.7°×29.1°×20.5°	

機械規格

	項目	描述		Tolerances
1	接口	CS		--
2	光學構成	9G		--
3	總長	50.19mm (W)		±0.20mm
4	法蘭後焦	12.526mm		--
5	法蘭後焦* (極限)	12.23mm (W) 13.23mm (T)		±0.10mm ±0.20mm
6	機械後焦*	6.69mm		±0.10mm
7	重量	51g		±10%
8	操作方式	變焦	手動	--
		對焦	手動	
		光圈	自動	

