



FEATURES :

- 8- Port 10/100M Switch with 4 PSE/PoE function ports (5-8 ports)
- Supporting the power Max. 30 W for each PSE/PoE port
- 19" rack-mount size
- Auto-detect full/half-duplex modes for any port
- Dedicated full-duplex 200Mbps bandwidth
- Store-and-Forward switching methods
- IEEE 802.3x flow control for full-duplex and back-pressure flow control for half-duplex
- Non-blocking full wire speed forwarding
- Auto-MDI/MDI-X function for any port

SPECIFICATION :

Standards	IEEE 802.3at /af / IEEE 802.3 10BaseT / IEEE 802.3u 100BaseTX / IEEE 802.3x Flow control
Filtering / Forwarding Rates	100Mbps port – 148,800pps / 10Mbps – 14,880pps"
Transmission Media	10BaseT Cat. 3, 4, 5 UTP/STP / 100BaseTX Cat. 5 UTP/STP"
LED Indicators	Per Port: LINK/ACT, PoE ACT/Status / Per Unit: Power"
Power Input	100 – 240V/AC, 50 – 60Hz
Power Output	48V/DC Per Port Output –30 W Max Per Port 4 Ports at Full 30 W Output Supported
Power Consumption	130 Watts (Max)
Dimensions	440 x 220 x 44 mm (L x W x H)
Weight	3.8 kg
Operating Temperature	0 to 45°C
Storage Temperature	-20 to 90°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class A, CE

DIMENSIONS : (Unit : mm)

440 x 220 x 44

