



SG1122LPR-H 1080P Day & Night Box IP Camera

www.meritlilin.com

- ▶ Full HD 2 megapixel MOS image sensor
- ▶ 60 fps@1080P True H.264 AVC High Profile video compression
- ▶ H.264 and Motion JPEG multi-profile video streaming
- ▶ 3D noise reduction (MCTF)
- ▶ 2D WDR function
- ▶ HDR function up to 100dB
- ▶ Digital PTZ supported
- ▶ IVS supported
- ▶ Motion detection, Tampering detection, audio detection, tripwire, object counting, traffic light detection function
- ▶ Smart event support
- ▶ Day & Night (IR cut removable)
- ▶ Built-in highly sensitive microphone
- ▶ 2-way audio supported
- ▶ Digital I/O : 1 in, 1 out
- ▶ ONVIF Profile S supported
- ▶ LPR System (License Plate Recognition Systems)
- ▶ RS-485 supported

Dimensions

70(W) × 50(H) × 135(D) mm

**Diagram of mounting holes:(unit in mm)**


Day and Night Operations via Removal of the IR-cut filter

SG1122LPR-H camera was designed using a mechanical IR cut filter for increased IR sensitivity resulting in improved night time images. The removable IR-cut filter allows day and night operations even in the low lux condition providing outstanding vision



Back Light Compensation

Back Light Compensation (BLC) adjusts the exposure of the entire image to properly expose the subject in the foreground. No matter if the main object is moving toward left, right, upper, lower, or any location in the screen, BLC provides perfect exposure for an object in front of strong back light



Sense Up+

Deliver outstanding video outputs in poor light conditions without experiencing motion blur. You can see video clearly even during nighttime without sufficient lighting support




3D Noise Reduction

Remove noise from a signal. Suppressing noise in an image in low light conditions and able to retain quality videos at the same time



Wide Dynamic Range (WDR)

Wide Dynamic Range (WDR) displays details of both the brightest and darkest areas. WDR can extend image visibility under high contrast lighting scenes and improve image quality



High Dynamic Range

An High Dynamic Range (HDR) image is made by taking 3 frames of the same scene and each at different shutter speeds to display details of both the darkest and brightest areas. HDR can extend image visibility under high contrast lighting scenes and improve image quality



Privacy Masking

Privacy Masking is a feature used to protect personal privacy by concealing private areas in the camera's field of view. Doorways and house windows for example are not subject to surveillance



Video Security App

Available on Android and iOS – LILIN Pro app provides security alarm push notification, real-time live viewing, and remote video playback



SD Cards in Sync with NAV Software

SG1122LPR-H camera with built-in Micro SD/SDHC/SDXC card slots can provide redundant video viewing and recording. You can synchronize an SD card with LILIN VMS (Video Management Software) – Navigator (NAV)



Advanced Motion Detection

Detect motion and capture the events. Motion in the selected area will provoke an alert. Time of motion in given direction can be detected by simply drawing an arrow on the video



Tripwire Detection

Tripwire Detection can be used where physical security is impractical or even impossible; i.e. railway tracks. An alarm can be enabled in either directions across the tripwire. Line Crossing that an object crossing a line drawn anywhere in the scene can be detected, and also Zone Intrusion that any arbitrary shape zone can be set to monitor intrusion



Object Counting

Object Counting is able to accurately to input images containing similar objects. Intelligent Object Counting technology includes People Counting feature – people enter or exit an area over time can be counted, as well as Vehicle Counting feature – to detect and track vehicle in real-time



Alarm Detection

Alarm Detection is designed to provide the electronic detection of intruders



Region of Interest (ROI)

A Region of Interest (ROI) is a specified part of an image that is highlighted from a camera. This feature is great for highlighting areas such as doors or areas of access where an overall scene is still required



1080P Day & Night Box IP Camera	
Video Performance	
Model	SG1122LPR-H
Min. Illumination	Color: 0.04 Lux at F1.2 ; B/W: 0.01 Lux at F1.2
Power and Environment	
Starting Temperature	-25°C – +50°C (-13°F – 122°F)
Operating Temperature	-25°C – +50°C (-13°F – 122°F)
Power Supply	DC12V ±10% / PoE (IEEE 802.3af compliant)
Power Consumption	DC12V, 7.2W / PoE, 8W
Sensor	
Pick Up Element	1/2.86" MOS image sensor
Effective Pixels	1952 (H) x 1266 (V) = 2,471,232 (pixels)
Certifications	
CE	Yes
FCC	Yes
PC Requirements	
CPU	Intel® Core™ i5 or higher grade
OS	Windows 7 or above
RAM	4GB or above Dedicated Graphics Card
Web browser	Microsoft® Internet Explorer® 9 or above
Mechanical	
Dimension	70(W) × 50(H) × 135(D) mm
Weight	420g approx.
Input / Output	
Audio Input / Output	Mono, 1.4 Vp-p, 50 KΩ, 3.5mm phone jack
Audio	Two-way Audio, G.711 u-law / PCM / AAC, Built-in Microphone
Alarm Input / Output	Digital 1 input (TTL, +3 – 5VDC) / 1 Output (MOS Relay contact N.O., Load max. 40VDC/300mA), Terminal connector
Live Video Output	CVBS 1.0Vp-p, 75 ohm, RCA connector
Video Streaming	
Video Compression	H.264 main and high profile, Motion JPEG
Video Streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast 4 configurable streams in H.264 and Motion JPEG, configurable frame rate, bandwidth Codec and GOP
Number of streams	4
Video Bitrate	128Kbps – 12Mbps; Frame rate and bit rate controllable on-the-fly; VBR / CBR / GOP supported; Fixed bitrate
Network Security	
Encryption	Base64 HTTP encryption, HTTPS encryption
Authentication	Digest HTTP authentication, RTSP authentication, 802.1x, DDNS via HTTPS
Address Filter	IP address filter, MAC address filter
Access	Multiple user access levels with password protection
User accounts	10 simultaneous users
Multi IP address	Yes
Video Resolutions (H x V)	
Resolution	2MP(1920 × 1080), 1.3MP(1280 × 960), 1MP(1280 × 720), D1(720 × 480, 720 × 576), VGA(640 × 480), CIF(352 × 240)
Maximum Frame Rate	Multi-stream mode, H.264 : up to 60 fps @ 1920 × 1080, MJPEG : up to 30 fps @ 720 × 480; HDR mode, H.264 : up to 30 fps @ 1920 × 1080 , MJPEG : up to 30 fps @ 720 × 480
Numeric Plate	
Multi IP address	Under 50KM/h
Countries	EU, UK, Russia ,Belgium, Bosnia, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Israel, Italy, Luxembourg, Macedonia, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Spain, Slovakia, United Kingdom, Vatican City, Slovenia, Sweden, Switzerland, Turkey, Armenia, Azerbaijan, Belarus, Estonia, Georgia, Kazakhstan, Latvia, Lithuania, Moldova, Turkmenistan, Ukraine, Uzbekistan / Plate number length supported: from 5 to 9 characters (A~Z and 0~9).

Numeric Plate	
Recognition	LPR Mapping Table: 1,000 groups of incorrectly recognized license plates can be edited to correct license plates Convert text O to 0 supported Convert text 0 to O supported Percentage of number plate width over screen width adjustable (6 to 30%)Scan
Video Functions	
Scanning System	Progressive Scan
Infrared Cut Filter	Auto / Day (Color) / Night (Mono) / Schedule
White Balance	Auto / Tungsten / Indoor / Fluorescents1 / Fluorescents2 / Outdoor1 / Custom
Back Light Compensation	On / Off
Electrical Shutter	1/30(1/25)s – 1/30000s
Sense Up	Off / 1 Frame / 2 Frames
Sense Up+	Yes
Auto Gain Control	60 dB Variable Gain
S/N Ratio	More than 50dB (AGC off)
3D Noise Reduction	Off / 1 – 32 Selectable
2D WDR	Off / Auto / x2 / x3 / x4 (by normal mode)
High Dynamic Range	Up to 100dB (by HDR mode, 2 shutter line interleave)
Privacy Masking	Off / On (4 zones)
Image Effects	Brightness, Contrast, Hue, Saturation, Sharpness, Mirror, Flip, Lens Distortion Correction, Defog
Integration	
Mobile Application	Integrated to LILIN mobile app (LILIN Pro) iPhone, iPad, Android support
Video Management	ONVIF Profile S, LILIN Navigator Enterprise 2.0, Third party VMS through LILIN HTTP API
SD Card Recording	Support Micro SD/SDHC/SDXC card for circular recording (card is not included)
Maintenance	Firmware update via HTTP and IP Scan; Firmware available at web site
IVS Advanced 2.0	Motion Detection, Tampering Detection, Advanced Motion Detection, Traffic Light Detection, Tripwire Detection, Object Counting
IVS Advanced 2.1 (Optional)	Unattended Object Detection, Missing Object Detection, Crowd Detection, Loitering Detection, Face Detection
Event Triggers	FTP / SMTP / HTTP post / SD card / SAMBA / SMTP Trap / Alarm Output
Alarm weighted mode	Motion / Tamper / Audio / Alarm / Network lost detection / Smart Event/ IVS / LPR
Control Interface	RS-485, Half duplex, Support MLP2, PELCO D/P communication protocol
Languages	English, Traditional Chinese, Simplified Chinese, Spanish, Italian, Turkish, Russian, Korean, French, Arabic, Hungarian, Japanese
Network	
Ethernet	10/100/1000 Mbps Base-T (Tx), RJ-45
ePTZ & Digital Zoom	Yes, ROI (Region of Interest)
OSD	Text overlay for date, time, and camera name
CPU, Memory	Embedded SoC, 500MHz Dual ARM Cortex-A9 & 500MHz ARM11, 1GB DDR3, 256MB flash memory
OS	Linux 3.8.8
Network Protocols	Pv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, SIP, MQTT, QoS, SNMP, SNMP Trap, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S, SDDP, Bonjour, 802.1x, SSL/TLS
Max number of online users	10 simultaneous users
Video Display	LILIN Universal ActiveX & HTML5
Numeric Plate Group	
Number plate lists	Log list: 1000 , all recognized car plate will be memorized, when log is full, data will be overwritten; allowed list can manually enter: 2000; denial list can manually enter: 100; visitor list: 2000; LPR Snapshot: 100 / Each list can have individual schedule and trigger specific events. / Holiday list is supported in schedule./ Effective-hours(start time and end time) are adjustable./ Support fuzzy recognition/ Detect level is adjustable (Very weak to strong)

