

DHD304A


4CH High Definition Analog Digital Video Recorder



FEATURES:

- 4 Channel AHD High Definition record
- Compatible to 960H analog camera
- UTC AHD camera supported
- Each channel independent record frame adjust
- Smart search playback with simulate high definition camera
- Mobile phone (iOS, Android) solutions provided
- QR Code APP scan, UID connection (Need additional option)
- Each channel 4 privacy mask area supported
- Up to 6TB HDD supported

360mm (W) × 307.63mm (L) × 60mm (H)



4CH 2M 2.0 High Definition Analog Digital Video Recorder

Model		DHD304A
Video Input	Supports	AHD / Analog camera
	Input	4 CH
	Simulation HD / Analog Camera Input Resolution	AHD 1080P / 720P and analog camera D1 / 960H
	Simulation HD / Analog Camera Maximum Input Frame Rate	1080P 120 / 100 FPS 720P 120 / 100 FPS 960H 120 / 100 FPS
Video output	Output	HDMI / VGA 1080P, CVBS
	Split Screen	1 / 4 split division, sequence mode, freeze
	Digital Zoom	Up to 5× on live and playback
	Privacy Mask	Each channel 4 privacy mask supported
Recording	Encode Format	H.264
	Resolution	CIF ~ 1080P
	Simulation HD / Analog Camera Maximum Recording Frame Rate	1080P 60 / 50 FPS 720P 120 / 100 FPS 960H 120 / 100 FPS
	Recording Mode	Continue, Schedule, Event
	Recording Schedule	4 schedule, 7day × 24 hours time table
	Alarm Event Actions	Adjustable motion area (100 level sensitivities) / System / Video loss
	Alarm Notification	Alarm notification iOS 、 android / E-Mail / FTP / Buzzer
Playback	Search	Event / Time / Smart search
	Display	4CH synchronous playback
	Resolution	CIF ~ 1080P
	Speed	Fast rewind 4×~32× / Fast forward 4×~32× / Step Forward / Slow motion 1/2~1/8
Storage	Internal HDD	1 × 3.5"HDD, 6TB supported
Backup	USB Flash Disk	Up to 32 GB supported
	Network Backup	Via HTTP
Audio	Analog Audio Input	1 CH, RCA × 1
	Audio Output	RCA × 1 (0.7Vp-p, 300 Hz to 3KHz)
Network	Ports	RJ-45 100Mbps × 1
	Protocols	TCP/IP, SMTP, HTTP, DHCP, PPPoE, NTP, DDNS
	Web	Direct internet browser access / Multiple users access
	Mobile Phone	iOS / Android supported
	P2P	QR Code APP scan / UID connection (Need additional option)
Software	VMS	CMS
	Backup / Playback	IE / Remote control software
	Reports	Alarm event, operation and configuration log full reports exporting over HTTP or USB
System	Authentication	User authentication with feature configurable
	Language	Arabic / Bulgarian / Chinese (Simplified) / Chinese (Traditional) / Croatian / Czech / Dutch / English / French / German / Greek / Hebrew / Indonesian / Italian / Japanese / Korean / Latvia / Persian / Polski / Portuguese / Romanian / Russian / Spanish / Thai / Turkish / Vietnamese
	HDD Inspection	S.M.A.R.T monitoring

	Recorded Reserve Time	Adjustable 1~9999 hours
	Time	Daylight saving / Time zone
Accessories	Mouse	Mouse click, drag and scroll
	Remote Controller	IR Remote controller(Need additional option)
	PTZ Protocols	RS-485 × 1, MLP1、MLP2、PELCO D、PELCO P、SAMSUNG、LG-MULTIX
	UTC	Up The Coax AHD camera supported
	WDT	Hardware watchdog timer
Others	CPU	ARM Cortex A9 Dual Core
	OS	Embedded Linux Kernel 3.1
	WDT	Hardware watchdog timer
Power and working environment	Power	Adapter DC 12V, 2.5A, 30W × 1
	Operating Temperature	0℃ ~ 45℃
	Operating Humidity	5% ~ 80%
	Dimension (W×L×H)	360× 316× 60 mm
	Weight	≈3 kg (Without hard drive)

No liability will be accepted for any errors or omissions. Design and specifications are subject to change without notice.